

AMB360, AMB500, AMB700

High Spin Hygienic Barrier Washer Extractors



FEATURES

- Freestanding, high spin
- Oversized frame, bearings and drum
- Large drain valve 2x Ø 76mm
- Easy access to all parts
- Frequency controlled motor
- Large door opening for easy loading and unloading
- Professional - fully programmable microprocessor
- Perforated lifting ribs: better washing results, lower water consumption
- Ecological washing programmes – significantly reduces water and electricity consumption
- Soap dispenser with 5 removable compartments
- RS485 & USB plug
- Designed with focus on ergonomics
- Patented inner door lock mechanism

OPTIONS

- Stainless steel cabinet
- Liquid soap pumps
- Weighing system for optimization of water and soap consumption
- Traceability software and networking system
- Isolation for energy and noise reduction
- Version without soap hopper
- Drain valve for water recycling
- Water sample tap
- Extra signalization of end of cycle
- Second display
- Lateral drain


DIMENSIONS & SPECIFICATIONS

HIGH SPIN HYGIENIC BARRIER WASHER EXTRACTORS


Model		AMB360	AMB500	AMB700
CAPACITY				
Drum capacity	kg/lb	36/79	50/110	70/154
Drum volume	l	360	500	700
Drum diameter	Ø mm		775	
Number of drums		1	1	2
Number of loading doors		1	1	2
Number of unloading doors		1	1	2
MOTOR				
Power	kW	4	7,5	7,5
DRUM SPEED				
Wash	rpm		41	
Extraction	rpm		900	
G-Factor			350	
PROGRAMMER				
Professional		standard	standard	standard
Cabinet				
Door opening angle	°		155	
HEATING				
100% hot water	°C		90	
100% electrical	kW	36	48	60
Steam high pressure	bar		3-8	
CONNECTION				
Electrical			3x200-240V 50/60Hz 3x380-415V 50/60Hz 3x440-480V 50/60Hz	
Water inlet	inch		3x 1"	
Steam inlet	inch		3/4"	
Drain diameter	inch		2x 3"	
DIMENSIONS				
HxWxD	mm	1700x1270x980	1700x1566x980	1700x2032x980
TRANSPORT DATA				
Gross	kg	1090	1280	1470
Net	kg	960	1130	1310
Packed HxWxD	mm	2005x1530x1255	2005x1830x1195	2005x2290x1195

*Tested in accordance of EN 604 56 norm. The data concerning dimensions of machines include all extended parts


Front AMB360 / AMB500



Front AMB700



Side AMB360 / AMB500 / AMB700



1. Emergency stop
2. Control panel
3. USB port
4. PC programming connection
5. Switch: steam / electric heating
6. Serial plate
7. Electrical signals liquid soap cover
8. Electrical components with frequency inverter cover
9. Main switch cover
10. Main switch
11. Equipotential bonding terminal