

LS 195 HP – LS 250 HP LS 300 HP – LS 350 HP

Industrial Tumble Dryers

FEATURES

- Heat pump
- Standard stainless steel drum with large diameter
- Easy-to-use microprocessor (Basic)
- Combination of Radial and Axial airflow - concept:
 - maximal heat transfer
 - low energy consumption
 - short drying time
- Very large door opening for easy loading and unloading
- Self cleaning lint screen

OPTIONS

- Coin operated version
- Reversing drum
- Full Control programmer (Professional)
- Residual moisture control:
 - safe drying of delicate linen
 - humidity detection in %
 - ideal in combination with wet cleaning
 - ideal for dry cleaners, fire depts
 - available on Basic and Professional control
- Stainless steel front
- Automatic rinsing system of condenser



DIMENSIONS & SPECIFICATIONS

INDUSTRIAL TUMBLE DRYERS

TYPE		LS 195 HP	LS 250 HP	LS 300 HP	LS 350 HP
CAPACITY					
Drum capacity	kg/lb	9/20	11/24	13/27	16/35
Drum volume	l	195	250	285	345
Drum diameter	mm	Ø760	Ø760	Ø760	Ø760
DRYING AVERAGE	g/min	122	126	120	120
MOTORS					
Fan	kW	0,20	0,20	0,20	0,20
Drive	kW	0,25	0,25	0,25	0,25
HEAT PUMP					
Electrical connection		3x380-415V 50Hz +N 1x 208-240V 50Hz (n/a for LS195HP) 1x 208-240V 60Hz (n/a for LS195HP) 3x 208-240V 50Hz 3x 400V + N 50Hz 3x 440V 60Hz			
Energy	kW	2,9	2,9	2,9	2,9
PROGRAMMER					
Basic control		Standard	Standard	Standard	Standard
Professional control		Available	Available	Available	Available
DIMENSIONS					
Size HxWxD	mm	1465x795x1275	1680x795x1525	1680x795x1615	1680x795x1735
TRANSPORT DATA					
Gross weight	kg	305	385	400	400
Net weight	kg	290	350	360	375
Packed HxWxD	mm	1570x880x1335	1785x855x1540	1785x855x1635	1785x855x1750

